

TABLE TOP



PROPERTIES

- Moisture resistance panel
- High resistance to scratches, shocks and abrasion
- High maintenance of color
- One decorative face and one counterbalance kraft paper
- Straight edge with 2 mm ABS edge band



APPLICATIONS

- Suitable for horizontal intensive usage (table, office desk, kitchen...)

RANGE

			
SIZE (mm)	1385x650	1650x850	1850x980
THICKNESS	28	28	28
PACK	10	10	10
PACKAGING	FULL PALET	FULL PALET	FULL PALET





TECHNICAL SPEC SHEET

TABLE TOP

TECHNICAL DATA SHEET

Mesured characteristics	Table / Horizontal use	Test method
Thickness	28 mm MR Complies with EN438 & DIN16926	
Wear resistance	Average wear ≥350 trs	NF D60 050 EN 438.2 DIN 53799
Choc resistance (500 gr ball)	Drop height : 65 cm 80% without break Ø impression ≤ 1cm	NF D 60 050
Scratch resistance	≥ 2 N	NF D 60 050 DIN 53799
Resistance to dry heat (180°C)	Degree ≥3 (according to EN 12 722 - 1 to 5 degree)	
Cigarette burning resistance	Light brown colour autorised	EN 438.2 DIN 53799
Resistance to hot liquids (cofee 80%)	Degree = 5 (1 to 5 degree)	NF D 60 050
Shade stability (blue nbr 6 exposed)	Grey contrast ≥ 4	
Glue holding	Class 3	
Delamination resistance	≥ 1.0 Mpa	NF EN 13329
Fire resistance	M3	Epiradiateur
Formaldehyde content	3,5 mg/m ² /h	ISO 12 460 - 3

All this information can be amended any time as needed.

Distributor stamp